

Minitron



This is Minitron

An all-round genius in a small space. In terms of capacity, the Minitron is the little sister of the Multitron incubation shaker, but it offers the same variety of application possibilities for microbial, animal, and plant cell cultures.



Two stacked units,
working height: 0.96 m

Cultivate up to 18 L

Compact footprint
of just 0.6 square meter

Perfect conditions for cultivation

The Minitron offers homogeneous conditions for reproducible results. Thanks to the ingenious design, the precise CO₂ regulation works with unparalleled efficiency. The meticulous sealing of the housing minimizes CO₂ consumption to a standard comparable to static incubators.

Seamless monitoring and control

The eve® platform software for bioprocesses can easily communicate with the Minitron via Ethernet. This technology gives you the freedom to monitor the cultures in the incubation shaker and control the device from anywhere via web interface. In addition, you can generate individual reports and document your processes in compliance with GMP.

Features

The Minitron can be used for cultivating microorganisms as well as cell cultures and is appropriately equipped for every area of application.

Drive unit

- Quiet, even and reliable for every load
- Dynamic equilibration ensures no manual adjustment is necessary
- Handling errors eliminated
- Easy to clean




Hygiene

- Easy-to-clean interior with rounded corners
- Base tray to retain liquid in the event of broken flasks
- Optional hygienic direct steam humidification




Connections and interfaces

- Reliable Ethernet interface for connecting eve® or process control systems
- Analogue outputs as an option connect to existing monitoring and alarm systems
- Pass-through for sensors and cables



Temperature regulation

- Precise regulation ensures homogeneous conditions for all batches
- Connection to existing laboratory cooling system possible
- Optionally integrated cooling for best use of space
- Excellent insulation ensures low energy consumption



Features



Technical data

	One unit	Two units
Dimensions (W x D x H)	800 mm x 625 mm x 700 mm	800 mm x 625 mm x 1490 mm
Maximum load	12 kg	24 kg
Volume	9 L	18 L
Maximum working height	173 mm	960 mm
Shaking throw		25 mm / 50 mm
Rotation speed		25 min ⁻¹ bis 400 min ⁻¹
Temperature range	5 °C above ambient temperature to 65 °C; 16 °C below AT to 65 °C with cooling; minimum temperature 4 °C	
Standard parameters	Temperature, rotation speed, timer	
Optional parameters	Cooling, CO ₂ regulation, humidification, light intensity	
Optional parameters	Ethernet	
Relative humidity (RH)	Up to 85% non-condensing	



Contact us and
we'll be happy
to advise you.



Contact
Worldwide

Sample configurations



Microorganisms

Maximum oxygenation even with maximum load stacked in two units

- Shaking throw of either 25 or 50 mm for optimal mixing, achieving comparable results in a range of vessels from microtiter plates to 5 L shake flasks
- High shaking speeds of up to 400 min⁻¹ for the best possible oxygenation

Cell cultures

Optimal conditions for mammalian and insect cells

- Active CO₂ regulation
- Hygienic direct steam humidification limits evaporation effects
- Meticulously sealed housing ensures low CO₂ consumption

Accessories

For automation, safety and flexibility, as well as requirements in the GMP environment.

Digital integration into the facility network

- Ethernet interface provides connectivity to eve[®] bioprocess platform software or 3rd party Process Control Systems
- Optional analog outputs

Qualification and process validation

- Design qualification
- Installation qualification
- Function qualification
- Factory Acceptance Test (FAT)
- Site Acceptance Test (SAT)
- Software validation for eve[®]

Trays

- Corrosion-resistant, anodized aluminum
- Can be loaded with a variety of retaining brackets, test tube holders, and adhesive matting
- Can be sterilized in the autoclave
- Special design for 96-well plates

Sticky Stuff adhesive matting

- Compatible with all vessels that have a flat base
- Reliable fixation even at high shaking speeds and temperatures
- Long lifespan
- Easy to clean and regenerate with water

Clamps

- Stainless steel retaining brackets can be screwed on to universal trays
- For Erlenmeyer and Fernbach flasks
- Special holders upon request

Test tube holders

- Foam rubber perforated inserts ensure a reliable hold and prevent rattling noises
- Test tubes can be incubated in a vertical position or at an adjustable angle
- Compatible with universal and Sticky Stuff trays

INFORS HT

We bring life to your laboratory

YOUR DISTRIBUTOR